

(12) **United States Patent**
Beardsley et al.

(10) **Patent No.:** **US 9,636,091 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **HAND-HELD ELECTROMECHANICAL SURGICAL SYSTEM**

(56) **References Cited**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **John Beardsley**, Wallingford, CT (US);
Matthew Chowanice, Middletown, CT (US);
Russell Pribanic, Roxbury, CT (US);
Paul Rinaldi, Wolcott, CT (US)

5,230,704 A 7/1993 Moberg et al.
5,499,992 A 3/1996 Meade et al.
(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

CN 102028509 A 4/2011
EP 0804124 B1 11/1997

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **14/983,689**

Chinese Office Action (with English translation) dated Dec. 25, 2015, corresponding to Chinese Application No. 201310012945.0; 16 total pages.

(22) Filed: **Dec. 30, 2015**

(Continued)

(65) **Prior Publication Data**

US 2016/0106401 A1 Apr. 21, 2016

Primary Examiner — Robert N Wieland

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/865,843, filed on Sep. 25, 2015, now Pat. No. 9,456,873, which
(Continued)

(51) **Int. Cl.**
A61B 18/18 (2006.01)
A61B 17/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/00** (2013.01); **A61B 17/068**
(2013.01); **A61B 17/07207** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 5/15188; A61B 2017/2931; A61B
2017/2925; A61B 2017/0046
See application file for complete search history.

(57) **ABSTRACT**

A hand-held electromechanical surgical device is configured to selectively connect with a surgical accessory. The surgical device includes a power-pack, an outer shell housing, and a gasket. The power-pack is configured to selectively control a surgical accessory. The outer shell housing includes a distal half-section and a proximal half-section, the distal half-section and the proximal half-section together defining a cavity configured to selectively encase substantially the entire power-pack therein. The gasket is located between the distal half-section and the proximal half-section of the outer shell housing. The gasket is configured to create a seal between the distal half-section and the proximal half-section and to provide a sterile barrier between the power-pack and an outside environment outside the outer shell housing.

14 Claims, 13 Drawing Sheets

